



MIRAI
by chimei

27
69cm

DTL-527V200
LCD TV



WWW.MIRAI.EU



...experience the future

27 DTL-527V200

69cm LCD TV

Screen Size	597.12(H) x 335.88(V)
Aspect Ratio	16 : 9
Pixel Pitch	0.4365(H) x 0.4365(V)mm
Panel Resolution	1366 x 768
Brightness	500 cd/m2
Contrast Ratio (typ.)	1200 : 1
Response Time (typ.)	6.5 ms
Viewing Angles (typ.)	1760(H) / 1760(V)
Standard TV	B/G, D/K, I, L/L=
Tuner System	PAL, SECAM, NTSC Video
Display Color	16.7 M
Control Panel	Power (On/Off), Source Select (TV/Video/SCART 1/SCART 2/SCART 2S/YPbPr/HDMI/PC), Menu(OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: CVBS/S-RGB (IN), TV (OUT) SCART 2: CVBS/S-RGB (IN), AV/TV (OUT) SCART 2S: S-Video (IN) VGA Input, PC Audio In (for VGA), HDMI, Headphone Output, Component Video (YPbPr)-R/L Input, Composite Video-R/L Input
Support Timing	480i / 480p / 576i / 576p / HDTV (720p / 1080i)
Speaker	5W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp, Red, Green, Blue, White Balance, Picture Mode, Aspect Ratio, Auto (picture setup), Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Program Edit, Audio (Balance, Bass, Treble, Surround), Language
Pic-Mode	User 1 / User 2 / Fantastic / Standard / Movie
PIP Function	Large and Small two window size options
Sleep Timer Function	Off / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	1000 Pages
Power Supply	AC 100-240 V, 2.4A, 50/60Hz
Power Consumption	Operation < 200W, Standby<1W
Safety / EMC	CB, TUV-GS, Gost-R, Nordics / CE / RoHS, WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord
VESA mounting	100 x 100 mm
System Dimension	680(W) x 515(H) x 158(T) mm
N.W.	11.5 kg

WWW.MIRAI.EU



...experience the future