

IBM System x3200 M2



Highlights

- **Manage growth and risk with configuration flexibility, data protection and application performance**
- **Manage complexity with integrated and remote management options**
- **Standard features deliver high levels of system availability—at a value price**

The IBM System x3200 M2 is a single-socket tower server that offers more performance, configuration flexibility and availability features than many servers in its class. It is designed to meet a wide range of business needs—and help you adapt to changing business requirements.

More configuration flexibility

The x3200 M2 offers the latest quad-core or dual-core processors. Providing up to 4.0 TB of disk storage, you can configure up to eight 2.5" hot-swap

SAS drives for added flexibility and performance. Integrated slotless hardware RAID and internal tape backup support help protect your valuable data.

Integrated management capabilities

The x3200 M2 provides integrated systems management through its mini-BMC2. Upgrade to the Remote Supervisor Adapter II SlimLine card to manage distributed systems remotely.

Greater business value

A proven platform that delivers performance and reliability, the x3200 M2 helps minimize costs, better manage complexity, and protect system investments.

Select configurations of the x3200 M2 are part of the IBM Express Advantage Portfolio™, designed and priced to meet the needs of mid-sized businesses. Easy to manage, Express models/configurations vary by country.

IBM System x3200 M2 at a glance

Form factor/height	Tower/5U (rack mountable)
Processor (CPU GHz/L2 cache/front-side bus MHz max)	Intel® Xeon® (quad-core) up to 3.0 GHz/12 MB/1333 MHz or Intel Xeon (dual-core) up to 3.0 GHz/6 MB/1333 MHz
Number of processors (std/max)	1/1
Memory ¹ (std/max)	512 MB or 2 GB/8 GB DDR II 667 or 800 MHz
Expansion slots	2 PCI (32-bit/33 MHz), 2 PCI-Express (x8, x1), optional PCI-X or hardware RAID-0, -1, Remote Supervisor Adapter II SlimLine slot
Disk bays (total/hot-swap)	Four 3.5" simple-swap or hot-swap SATA, four 2.5"/3.5" hot-swap SAS or eight 2.5" hot-swap SAS hard disk drives (HDDs)
Maximum internal storage ^{1,2}	Up to 1.17 TB SAS or up to 4.0 TB SATA HDDs
Network interface	Integrated Gigabit Ethernet
Power supply (std/max)	400W 1/1 or 430W hot-swap redundant 2/2
RAID support	Hot-swap hardware RAID-0, -1, upgrade to RAID-5
Ports	Six USB; Ethernet, two serial, parallel and video
Systems management	IPMI 2.0-compliant mini-BMC2, IBM Director, Alert Standard Format 2.0, IBM ServerGuide™, optional RSA II SlimLine and Remote Deployment Manager
Operating systems supported	Microsoft® Windows Server® 2003 and 2008, Windows® Small Business Server 2003, Red Hat Linux®, SUSE Linux
Limited warranty ³	1-year or 3-year customer replaceable unit and onsite limited warranty

For more information

U.S.	ibm.com/systems/x
Canada	ibm.com/ca/en/systems/x

¹ Maximum internal hard disk and memory capacities may require the replacement of any standard hard drives and/or memory and the population of all hard disk bays and memory slots with the largest currently supported drives available. When referring to variable speed CD-ROMs, CD-Rs, CD-RWs and DVDs, actual playback speed will vary and is often less than the maximum possible.

² When referring to storage capacity, GB = 1,000,000,000 bytes, and TB = 1,000,000,000,000 bytes. Accessible capacity is less.

³ IBM hardware products are made from new parts, or new and serviceable used parts. Regardless, our warranty terms apply. For a copy of applicable product warranties, write to: Warranty Information, P.O. Box 12195, RTP, NC 27709, Attn: Dept. JDJA/B203. IBM makes no representation or warranty regarding third-party products or services including those designated as ServerProven® or ClusterProven®.



© Copyright IBM Corporation 2008

IBM Systems and Technology Group
Route 100
Somers, New York 10589

Produced in the United States
August 2008
All Rights Reserved

This publication could include technical inaccuracies or typographical errors. This publication was produced in the United States. IBM may not offer the products, services or features discussed in this document in other countries, and the information may be subject to change without notice. References herein to IBM products and services do not imply that IBM intends to make them available in other countries. Consult your local IBM business contact for information on the product or services available in your area.

Information about non-IBM products is obtained from the manufacturers of those products or their published announcements. IBM has not tested those products and cannot confirm the performance, compatibility, or any other claims related to non-IBM products. Questions on the capabilities of non-IBM products should be addressed to the suppliers of those products.

IBM, the IBM logo, ibm.com and System x are trademarks or registered trademarks of IBM Corporation in the United States, other countries or both. If these and other IBM trademarked terms are marked on their first occurrence in this information with a trademark symbol (® or ™), these symbols indicate U.S. registered or common law trademarks owned by IBM at the time this information was published. Such trademarks may also be registered or common law trademarks in other countries. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at ibm.com/legal/copytrade.shtml.

Intel and Xeon are trademarks or registered trademarks of Intel Corporation or its subsidiaries in the United States, other countries or both.

Linux is a registered trademark of Linus Torvalds in the United States, other countries or both.

Microsoft, Windows and Windows Server are trademarks or registered trademarks of Microsoft Corporation in the United States, other countries or both.

Other company, product and service names may be trademarks or service marks of others.